

# Orthoflex




RECYCLING



POLYMER


## Highlights

- Easy workable
- 25% recycled material
- Fully recyclable




back

## Properties



## ADHESIVE

Both sides / Polyester  
in compound



## DELIVERY

1.10 x 1.40 m / 0.70 x 1.10 m



## CUTTING

Diagonally

**Copolymer core of synthetic resins. High range of thermoplastic toe puffs and counters that meets the highest quality requirements, combines an excellent shape retention (up to 95%), resilience and durability even after intense use.**

- Guarantees the maximum adhesion on both sides, even in the skived area.
- Great versatility, optimal behaviour in flat counters as in pre-moulded

## Material Data

Types	Thickness	Size
Orthoflex	1,1 mm	1.10 x 1.40 m
Orthoflex	1,6 mm	1.10 x 1.40 m
Orthoflex	1,1 mm	0.70 x 1.10 m
Orthoflex	1,6 mm	0.70 x 1.10 m

## Processing

Moulding pressure: 4-5 kg/cm  
Processing time: 2-3 minutes after activation  
Final hardness: minimum of 24 hours

Bonding conditions may vary according the type of upper

## For medical device Class 1

According (EU) MDR 2017/745



## Reinforcements

Manufacturer's warranty & storing: When working with multiple materials during processing, chemical reactions and incompatibilities between components should always be tested beforehand. We are not liable for damage caused by failure to follow our instructions or responses beyond our influence and control. Under normal conditions, storage is unlimited, but avoid storage in direct sun. The goods are guaranteed for 6 months from the date of delivery.

[www.frecoma.nl](http://www.frecoma.nl)